





TRIO CRP & CRPS Permanent Magnets

Powerful Self-Cleaning and Stationary Permanent Magnets

Building Solutions Together

WWW.TRIOPRODUCTS.COM

Permanent magnets offer an economical ferrous removal solution requiring no electric power and the belts driven either by electric or hydraulic power.

TRIO's powerful self-cleaning permanent magnets are suspended overhead, mounted in heavy-duty steel frames and traversed by a heavy-duty vulcanized armored belt running on two pulleys. With superior build quality, producers world wide continue to experienc improved service life of critical components.

Applications


- Midecholition debris
- Crusbedroken concrete
- Haardk crushing
- Miscelids at MRF facilities
- Shred die ds
- Organoimpositing



CRP and CRPS Series Features


- Overhead-suspendeedf-cleaning permanent magnets
- Heavy-dsteel frames
- Torudey design
- Elecorichydraulic motors
- Magreequires no electrical source
- **FP**M belt speed (variable)
- Stainbergel armored belting
- Cross-beld in-line configurations
- One-warranty
- Continuie gvice commitment

Permanent Magnets




Model	Magnet Size	Size W x L MM	Weight		Gauss	Gauss	Gauss @	Maximum Effective		Distance fo	Distance for 1/2" Nut		Motor Power	
			LBS	Kg	@ 6"	@ 9"	Gauss @ 12"	Inch	мм	In	мм	HP	KW	
CRP30	30" x 36"	762x915	2100	953	1000	540	400	14"	355	9"	228	3	2.2	
CRP ₃ 6	36" x 42"	915x1067	3600	1633	1230	840	520	14"	355	9"	228	3	2.2	
CRP42	42" x 48"	1067x1220	4750	2155	1420	980	650	14"	355	9"	228	3	2.2	
CRP48	48" × 54"	1220X1370	6300	2858	1470	1050	750	14"	355	9"	228	3	2.2	
CRP54	54" x 60"	1370X1524	7400	3357	1520	1150	870	14"	355	9"	228	3	2.2	

Model	Magnet Size	Size W x L MM	Weight		Gauss	Gauss	Gauss @	Maximum Effective Range		Distance for 1/2" Nut	
			LBS	Kg	@ 6"	@ 9"	12"	Inch	мм	In	ММ
CRPS30	30" x 36"	762x915	1000	454	1000	540	400	14"	355	9"	228
CRPS ₃ 6	36" x 42"	915x1067	2000	907	1230	840	520	14"	355	9"	228
CRPS42	42" x 48"	1067x1220	3000	1361	1420	980	650	14"	355	9"	228
CRPS48	48" × 54"	1220X1370	4000	1814	1470	1050	750	14"	355	9"	228
CRPS54	54" x 60"	1370X1524	5000	2250	1520	1150	870	14"	355	9"	228



TRIOPRODUCTS.COM

Data for marketing purposes only. Please contact TRIO for product information. Capacities are suggested only and wholly dependent on material type and condition.









TRIO Builds Standard and Customized Solutions for Your Application Needs.

Whether it's feeders, crushers, washers, screens, conveyors, or complete plants, TRIO is known around the world for innovative engineering and unmatched value. Built to withstand the most demanding mine and quarry environments, TRIO helps companies meet their operational requirements on time and on budget.

TRIO sets a standard for responsiveness and flexibility in the industry, building the kind of relationships that the competition just can't match. Contact TRIO today to find about more about our range of durable, productive, highly-efficient and cost-effective aggregate and mining equipment.

VISIT WWW.TRIOPRODUCTS.COM FOR MORE INFORMATION

US +1 626 851 3966

EU +353 57 86 61333

